

## MODEL – VERSION: COMPACT MULTIPLEX

Description	Mesures
Length of machine	2,80 [m]
Width	1,46 [m]
Minimum - maximum platform height	1,00 – 2,90 [m]
Minimum - maximum platform width (inclined parapets)	1,30 – 2,80 [m]
Length of platform	2,60 [m]
Batterie's voltage	48 [V]
Power of single traction motor	5 [kW]
Motor's power hydraulic pump	2 [kW]
Battery's capacity	300 [Ah]
Payload on platform total	900 [kg]
Payload on central platform	500 [kg]
	600 [kg]
Payload on lateral platforms - total	6 people
Payload on single lateral platform	300 [kg]
	3 people
Maximum lateral platforms extension	60 [cm]
Maximum lateral working slope	15%
Maximum longitudinal working slope	20%
Recharge's voltage	240 [V]
Maximum speed of wind	12,5 [m/s]
Belts for harvesting Multi-02	
Width of single platform	40 [cm]
Length of single platform	1,25 [m]
Payload single platform	160 [kg]
	2 people
Minimum - maximum platform height	1,10 – 1,90 [m]
Maximum lateral platform extension	60 [cm]
Minimum - maximum width of machine (with closed platforms – platforms at maximum extension)	1,55 – 2,75 [m]
Payload of bins unloading forklift	400 [kg]